

PTZ series | Outdoor PTZ Camera

IPS4304EA/4308EA

30X Day & Night 30fps Full HD PTZ Dome IP Camera

www.meritlilin.com



The IPS4304EA / IPS4308EA is outdoor fitted Day & Night 1080P Full HD PTZ Dome IP camera. The high-speed dome is capable of streaming HD video at up to 30 FPS. Featuring Wide Dynamic Range (WDR) feature, the IPS4304EA / IPS4308EA captures highlights and shadows simultaneously, eliminating pixilation and smear. Combine this with 3D Noise Reduction technology and adaptive tone reproduction and the contrast of images in bright or dark areas is dramatically improved. Capable of making 360° continuous rotations, users can accurately position the camera to identify specific targets. The 30x optical zoom gives the IPS4304EA / IPS4308EA an impressive range. With a focal length of 4.3mm-129mm, an IP66 weatherproof rating and a compact design, the IPS4304EA / IPS4308EA is ideal for numerous applications.




- ▶ Outdoor PTZ camera
- ▶ 30X optical zoom
- ▶ IP66 rain and dust resistant
- ▶ IR cut filter for day/night operations
- ▶ 1080p HD resolution
- ▶ Wide Dynamic Range up to 90dB
- ▶ IK10 impact resistant

Dimensions: Ø 210 x 332mm




Diagram of mounting holes (unit in mm):



Mounting Options	
Wall Mount	BTS03G
	PIH-520LB
Wall Mount	PIH-520L
	PIH-520G
Swan Neck	PIH-520HB
Pendant Mount	BTS06W


PTZ Control Function

Pan-Tilt-Zoom (PTZ) cameras are able to perform remote directional and zoom control. Capable of making 360° continuous rotations and 102° tilt angle, the cameras field of view can be quickly zoomed and repositioned as needed to identify specific targets



30X Optical Zoom

Remote pan/tilt/zoom operations with 30X optical lens makes it possible to zoom in on distant object with absolute clarity



Video Security App

Available on Android and iOS – **LILINViewer** app provides security alarm push notification, real-time live viewing, and remote video playback



Day and Night Operations via Removal of the IR-cut filter

IPS4304EA / 4308EA camera was designed using a mechanical IR cut filter for increased IR sensitivity resulting in improved night time images. The removable IR-cut filter allows day and night operations even in the low lux condition providing outstanding vision



SD Cards in Sync with NAV Software

IPS4304EA / 4308EA camera with built-in Micro SD/SDHC/SDXC card slots can provide redundant video viewing and recording. You can synchronise an SD card with LILIN VMS (Video Management Software) – Navigator (NAV)



Motion Detection

Detect motion and capture the event. Motion in the selected area will provoke an alert



Wind and Rain Standards

Meet international IP66 standards for dust and moisture resistant allowing you to install cameras in environments subject to wind and rain



Two-way Audio Support

With 2-way audio communication, you can project your voice through the camera's speaker instead of hearing what's going on (1-way audio)



ONVIF-compliant

Open Network Video Interface Forum (ONVIF) is a standard for physical IP based security products. IPS4304EA / 4308EA PTZ camera is ONVIF Profile S conformant



Wide Dynamic Range (WDR)

Wide Dynamic Range (WDR) displays details of both the brightest and darkest areas. WDR can extend image visibility under high contrast lighting scenes and improve image quality



Alarm Detection

Alarm Detection is designed to provide the electronic detection of intruders




Noise Reduction

Remove noise from a signal. Suppressing noise in an image in low light conditions and able to retain quality videos at the same time



Back Light Compensation

Back Light Compensation (BLC) adjusts the exposure of the entire image to properly expose the subject in the foreground. No matter if the main object is moving toward left, right, upper, lower, or any location in the screen, BLC provides perfect exposure for an object in front of strong back light



IK10 Impact Resistant

IK10-certified housing designed to protect the camera from destructive behavior



30X Day&Night 1080P Full HD PTZ Dome IP Camera

Video performance

Model#	IPS4304EA	IPS4308EA
Low Light Mode (Colour)	0.5 lux (1/30 sec, F1.6(Wide), 50IRE, AGC-Gain: 30dB ICR-OFF) 0.1 lux (1/30 sec, F1.6(Wide), 50IRE, AGC-Gain: 30dB ICR-OFF) 0.2 lux (1/8 sec, F1.6(Wide), 50IRE, AGC-Gain: 30dB ICR-OFF) 0.01 lux (1/8 sec, F1.6(Wide), 50IRE, AGC-Gain: 30dB ICR-OFF)	
High Dynamic Range	Upto90dB	

Power

Model#	IPS4304EA	IPS4308EA
Power consumption	37W (with heater) / PoE+ 14W(does not support the heater)	48W (with Heater) / PoE+ 14W (does not support the heater)
PoE+	High power PoE	
Power supply	AC24V Power over Ethernet+	AC100-240V Power over Ethernet+

Sensor

Sensor type	1/2.8" CMOS image sensor
Effective pixels	1944 (H) x 1224 (V) = 2,379,456 (pixels)
Total number of pixels	1952 (H) x 1236 (V) = 2,412,672 (pixels)

Certifications

CE	Yes
FCC	Yes
IP Rating	IP66 waterproof
Vandal resistant rating	IK10 impact resistant

Lens

Zoom ratio	30X optical zoom
Focal length	4.3mm (WIDE) - 129mm (TELE)
Minimum aperture ratio	1:1.6 (WIDE)-5.0 (TELE)
Minimum object distance	10cm (WIDE end), 1.5m (TELE end)
Iris range	F1.6 - 32, close
Angle field of view	Approx. 64.45°(H) 39.27°(V) (WIDE end), approx. 2.41°(H) 1.36°(V) (TELE end), (1080p mode)

Pan & Tilt

Panning range	360° Endless
Panning mode	Manual, Auto, Manual Position, Sequential Position
Panning speed	Manual Approx. 0.1°/s - 120°/s 8 Steps, Preset Approx. 1°/s - 255°/s, Alarm Trigger Speed 360°/s
Tilting range	-6° - +96°
Tilting mode	Manual, Auto, Manual Position, Sequential Position
Tilting speed	Manual approx. 0.15°/s-120°/s 8 Steps, 16 Steps / Preset approx. 1°/s-255°/s, Alarm Trigger Speed 360°/s

Environmental

Ambient operating temperature	-10°C-+ 50°C (14°F-122°F) / PoE+ - 40°C-+ 50°C (-40°F-122°F) / AC
Operating humidity	0%-90%

PC requirement

CPU	Intel Core 2 Duo E6400 2.13GHz or above
OS	Windows 7 or above
RAM	4GB or above, Dedicated Graphics Card
Web browser	Microsoft® Internet Explorer® 9.0 and later

Mechanical

Dimensions (H x D)	332 (H) x 210 (D) mm
Weight	3200g approx.

Video streaming

Video compression	H.264, Motion JPEG
Streaming	RTP/HTTP, RTP/TCP, RTP/UDP, Multicast
Bitrate	128 Kbps to 8 Mbps Frame rate and bitrate controllable on-the-fly VBR / CBR / GOP supported

Video resolution (H x V)

1080p HD	1920 x 1080
720p HD	1280 x 720
D1	720 x 480, 720 x 576
CIF	352 x 240
Frame rate	H.264: up to 30FPS @ 1920 x 1080 Motion JPEG: up to 30FPS @ 720 x 480

Video functions

Day/Night (IR-cut filter)	Colour (Day), Monochrome (Night), Auto
Scanning system	Progressive scan
White balance	ATW/Indoor(3200K)/Outdoor(5800K) /Manual(1800K ~10500K)
Shutter	Auto / manual(1/1 to 1/100,000)
Exposure mode	Auto / Manual
Back light compensation	Off / BLC / WDR
Digital noise reduction	Off / On (2D, 3D)
Dynamic privacy zone mask	Off / On (up to 16 areas)
Auto mode	Off / AUTO / SEQ / TOUR
Web PTZ control	Pan, tilt, zoom-in / zoom-out, absolute position, and mouse click function
Schedule setting	Off / Auto Mode / Preset position
Auto gain control	50dB Variable Gain
Image Effects	Contrast, Sharpness, Mirror, Flip, Defog, DIS, Digital Zoom(x16)

Integration

Mobile application	Integrated to LILIN mobile app (LILINViewer) iPhone, iPad, Android support
Video management	ONVIF Profile S LILIN Navigator Enterprise 1.0 and 2.0 Third party VMS through LILIN HTTP API
SD card recording	Support Micro SD/SDHC/SDXC card for circular recording (card is not included)
Firmware	Firmware upgrade via HTTP Firmware available to download at meritlilin.com
IVS Basic 1.0	Motion Detection, Audio detection
Alarm event triggers	Alarm / motion / audio / Network lost detection
Alarm event actions	FTP, HTTP post, SD card
Alarm weighted mode	Support

Network

Ethernet	10Mbps / 100Mbps, RJ-45
Connectivity	ONVIF Profile S
Users	10 simultaneous users
ePTZ & Digital Zoom	16X
OSD	Text overlay for date, time, and camera name, and PTZ position
CPU, Memory	Embedded SoC ARM11, 528MHz, 256MB DDR2, 256MB flash memory
Video display	LILIN Universal ActiveX & LILIN Java Applet
OS	Embedded Linux 2.6.32
2-way audio	G.711
Protocols	IPv4, IPv6, TCP, UDP, HTTP, SMTP, NTP, DDNS, UPnP, FTP, ARP, DHCP, PPPoE, DNS, Telnet, RTSP, RTCP, ONVIF profile S, SNMP, Bonjour
IP Filter	Yes
Multi IP address	Yes

Network security

User accounts	10 users accounts available
Access	Multiple user access levels with password protection
Encryption	Base 64 HTTP encryption
Authentication	Digest HTTP authentication, RTSP authentication

Heater & Fan	
Heater activation	On: 15°C, Off: 25°C
Fan activation	On: 35°C, Off: 25°C

Main functions	
Control function	Pan and Tilt / Zoom and Focus / Iris and ICR / 128 Preset Position / Home Position
Digital zoom ratio	16X
Zoom speed	0 ~ 7 Selectable [Fast : Approx. 6.0 Second (Tele to Wide) in Manual Mode]
Focus speed	0 ~ 7 Selectable [Fast : Approx. 6.0 Second (Far to Near) in Manual Mode]
Focus	Auto (Continue / Interval / Zoom Trigger / One Push), Manual Focus
Iris Control	DC IRIS , ALC (Adjustable Output Target Level) / Manual

Input / output	
Alarm input / output	6 Input (TTL 5Vdc), 2 Output (0.5A 120Vac, 1A 24Vac)
Video output	CVBS 1.0 Vp-p / 75 Ω BNC