

Navigator 2.0 Corporate

Navigator 2.0 Corporate 108CH



LILIN VMS software – Navigator 2.0 Corporate records and manages up to 108 cameras of H.265/H.264/MJPEG HD IP cameras or DVR's / NVR's cameras. It can also support up to 108 channels IP cameras on multiple monitors for TV Wall application. Navigator 2.0 Corporate supports NAV Control Center which includes NVR P2P, centralized user management, centralized alarm management, centralized device management, eMap Center and Mosaic TVWall. To raise awareness on the situation of the environment, it is highly recommended to install Navigator 2.0 Corporate at security managers' office and security control command center.

Features

- Manage and record 108 IP cameras per station
- Integrated alarm management for various alarm outputs
- User-friendly UI and TV Wall application are supported
- 64bits program
- ONVIF Profiles S compliant
- System redundancy
- Advanced alarm scheduling & logic
- Hierarchical control center to manage multiple stations
- Central Alarm management with TV wall and eMap
- Support 4K UHD camera, 120FPS camera
- Support corridor mode and panoramic cameras
- Support web client.
- iPhone, iPad & Android support
- Perfect software for security checkpoints of corporate group to perform flawless remote monitoring



Navigator 2.0 Corporate 108CH

Navigator Corporate	
Application	64bits

Recording	
Recording	Schedule / Motion detection / Manual recording
Live	Up to 108 channels
Speed	Up to 400Mbps upload and download
Resolution	Up to 4K 30FPS and 2MP at 120FPS
Schedule	7 day * 24 hrs time table, recording mode configurable
Alarm recording	Face detection, audio detection, tampering, motion, DI alarm detection
ONVIF	Licensing
NAS	Yes
RAID failure notification	LSI driver integrated

Playback	
Playback	Time search, event search, date search, POS SmartSearch and motion SmartSearch
Speed	FR: 1/8, 1/4, 1/2, 1X, 2X, 4X, 8X, 16X, 32X / FF: 1/8, 1/4, 1/2, 1X, 2X, 4X, 8X, 16X, 32X
Compression	H.265/H.264/MJPEG
Search	Date, time, event, POS SmartSearch, motion SmartSearch, plate search (optional), record tagging
Tagging	Video tagging for overwritten protection
Multiple channel playback	Up to 36 channels & grouping playback
Remote playback	Remote multiple channel playback for SD card, NVR/DVR, and Navigator

Video input	
Video Input	LILIN IP camera, LILIN IP speed dome, LILIN DVR/NVR, Navigator Software live server
Camera name	20 characters
Channel editing	Mouse drag-n-drop
Digital zoom	Yes, ePTZ supported for live and playback
Low bandwidth mode	JPEG snapshot input and record
Multiplexer	Sequence
Split screen	4, 9, 16, 25, 36
2 x 2 video wall	Yes
Network TV wall	Up to 1000 rooms, 144 monitors per room, 1000 channel groups per room, 144 channels per group
Video decoder	LILIN VD022 for video wall
Corridor mode	Yes
Monitor outputs	Up to 8 monitors

Alarm	
Alarm management	PC sound, redirect IP camera DO, eMail snapshots, redirect a PTZ preset recall
Event	Various alarm log, video loss, stop recording, schedule, logon, operation log
Digital output	Third party TCP/IP digital output supported.
Alarm scheduling	Up to four alarm tables with AND logic
Central management	Watching alarms from multiple stations

Accessories	
P/T/Z protocol	ONVIF PTZ Supported
Audio	PCM/G.711, two-way audio, audio recording
POS/barcode Scan/ATM	Third party TCP/IP RS-232 supported
Keyboard	PIH-931D keyboard controllable via RS-485 for PTZ, ePTZ, and ROI features
Number plate recognition	Optional

eMap	
eMap live monitoring	Four channel for IP camera/multi-channel for NVR/DVR
PTZ control	Yes
Alarm	Digital output controllable, snapshots, and alarm popup

Central management	Watching cameras from multiple stations
Online Maps	Google Map and Baidu Map, GPS devices supported

DB Manager	
Database	Database configuration database import & export, CVS file, report, and maintenance
Event search filter	Yes
Central management	Event logs from multiple stations

Remote Access	
Remote NAV Live video	Multiple channels of HD, SD, and low bitrate modes supported
Remote DVR/NVR video	Multiple channels of DVR/NVR supported

Backup	
NAV/DVR/NVR	DVR remote backup, AVI conversion and JPEG snapshots
Remote backup	Multiple channels remote backup supported
Failure over	Up to 108 channels for 4 Navigators
Archiving	Yes

Management	
Access log	Complete access log in database manager
User management	Up to 512 user groups, each of which supports 1000 user that possess access privileges according to functions and device settings
Recording calculator	Yes, dynamically calculating available recording days
Navigator Client	Yes

Network	
Web interface	Live web interface
Mobile phone	iPhone and Android
Protocols	ARP / TCP/IP / RTSP / ONVIF / HTTP / SMTP / DNS / PPPoE
Max of client connects	Up to 300
IPScan	Supported, easy-to-setup for IP address

Other	
DST	Daylight saving time by Windows OS
Time sync	IP camera and NVR
OS	Windows 7/8/10 64 bits
Language	English, Chinese, Spanish, French, Italian, Japanese, Russian, Portuguese, Simplified Chinese, Czech, Slovene, German, Turkey, Hungarian, and Arabic
CPU requirement	Intel E5 or I7 recommend
RAM requirement	8GB memory