

NVR6208E 8 CH PoE 4K Standalone Network Video Recorder

www.meritlilin.com



- ▶ Taiwan chipset
- ▶ NDAA Compliant
- ▶ 8 Channel H.264/H.265 network camera Input
- ▶ Up to 4K H.264/H.265 network camera support
- ▶ 8 Port PoE, automatic network camera plug and play
- ▶ Internal HDD up to 12TB supported
- ▶ P2P QR code UID connection for APP and Navigator
- ▶ Network maximum input through up to 64Mbps

Introduction

The NVR6208E standalone NVR is the next generation of LILIN professional PoE NVR series. No IP addresses' configuration for cameras is needed. The NVR6208E is built-in PoE for powering PoE cameras. The NVR6208E supports up to 8 channels Ultra HD (4K) camera recording that the Ultra High Definition, 4K or 8 Megapixels video is four times clearer than traditional 1080p. Along with its low power consumption and all-in-one sleek design, the NVR6208E provides users a simple, affordable yet professional solution for megapixel surveillance in the mainstream markets such as SMBs, retail, hospitality, and intelligent buildings.

Adapted to ONVIF-compliant IP cameras

NVR6208E is an easy-to-install Linux based standalone HD solution can record ONVIF compatible cameras



Instant Notifications

When an event occurs and the alarm recording is enabled, an alarm icon will be shown instantly on the monitoring display unit and front panel OLED display



Timeline-based Search

Operators may easily distinguish regular and alarm recording on the intuitive time line playback bar



Remote Viewing

Remote viewing from handheld devices is fully enabled, with iOS and Android compatibility. LILINViewer app provides security alarm push notification, real-time live viewing and remote video playback



P2P

P2P is an easy-to-use service that allows users to access a LILIN NVR by simply scanning a QR code with your smartphone camera. With P2P, you will no longer set up port forwarding in the router, and the use of a P2P driver enables you to access two-way audio, video playback, IO control, and even PTZ control.



Plug-n-play Device

An automated installation wizard, IPScan and WS Discovery, locates all the cameras on the network and imports a preview picture of each channel to help with identification



Email Notification

LILIN NVR can send email notification with snapshot as an attachment in JPEG to one or multiple recipients in case of any event



8 CH PoE 4K Standalone Network Video Recorder

IP video input	
Model	NVR6208E
Supports	Network camera / ONVIF Profile S / DVR / NVR / Video encoder / Navigator
Input	8 CH
Resolution	4K / 5M / 4M / 3M / 1080P / 1.3M / 1M / 960H / D1 / VGA / CIF
Maximum Frame Rate	240 FPS

Video output	
Output	HDMI 1.4 (4K 30P) / VGA 1080P
Spot Monitor	HDMI & VGA sync output
Split Screen	1 / 4 / 8 / 9 split division, sequence mode, freeze, alarm display
Digital Zoom	Up to 64x on live and playback

Recording	
Encode Format	H.264 / H.265
Maximum Network Throughput	64Mbps
Resolution	CIF ~ 4K
Frame Rate	Single channel up to 1080P 60 FPS record
Recording Mode	Manual, schedule (continue, event, none)
Recording Schedule	Each channel 7day × 24 hours time table, recording mode configurable
Alarm Event Actions	Motion grid (20×12, multi-level sensitivities) / network camera event / DI
Metadata options	POS RFID AND PIN CONTROLLER USER DEFINED 2 BARCODE SCANNER GPS LPR (Denial, Allowed, Visitor)
Alarm Notification	Alarm notification iOS · android / E-Mail / FTP / buzzer / DO

Playback	
Search	Alarm event / Operation event / System event / Meta data event / Time search
Display	8CH synchronous playback
Resolution	CIF ~ 4K
Max. Frame Rate	Up to 1080P 60FPS
Speed	Fast rewind 2x ~ 64x / Fast forward 2x ~ 64x / Slow motion 1/2 ~ 1/16

Storage	
Internal HDD / Swap Drive Bay	2 × 3.5 HDD(Up to 12 TB supported)

Backup	
USB Flash Disk	Up to 128 GB supported
Network Backup	Via HTTP / FTP / Network Places
DVD DVD/RW	External USB DVD / RW

Audio	
Audio Input	8 CH (Network camera), G.711 u-law 8K & AAC
Audio Output	RCA × 1 (0.7Vp-p, 300 Hz to 3KHz)
Network Camera Two Way Audio	Yes

Network	
Ports	RJ-45 Gigabit Ethernet × 1, RJ-45 100Mbps PoE × 8 (802.3af)
Protocols	ARP / TCP/IP / UDP / HTTP / HTTPS / SMTP / SNMP / FTP / DDNS / PPPoE / NTP / RTP / RTSP / DHCP / ONVIF Profile S
Web	Direct internet browser access / Multiple users access
Mobile Phone	iOS / Android supported
P2P	APP scan QR Code / UID connection
RTSP Service	RTP UDP/ RTSP TCP supported
IPScan / WS-Discovery	Network camera plug and play via PoE port, otherwise WS-Discovery and IP Scan, automatically quick IP address setup for network cameras also available
Web access	Live / playback / backup / menu configuration / event log

Software	
VMS	Navigator
Backup / Playback	Remote Playback Manager / Backupman, multiple NVRs file download and multi-channel playback

Alarm	
Alarm/event (Ports)	DI × 8 and DO × 1 (With programmable condition)

System	
Reports	Alarm event, operation, configuration and system execution log full reports exporting over HTTP or USB
Authentication	User authentication with feature configurable and IP address blocking
Language	Arabic, Traditional Chinese, Simplified Chinese, English, French, German, Hungarian, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Turkish
HDD Inspection	S.M.A.R.T monitoring / File system de-fragmentation/ IO read write error
Recording Day	Automatic recording day calculator
Time	Daylight saving / NTP / External USB GPS time sync / Keyboard

Accessories	
PTZ Protocols	HTTP / ONVIF
Keyboard	Support PIH-931D keyboard input (Connector box required)
USB to RS-232	Record external metadata via USB to RS-232 cable, display at live and playback
RS-485	One set for keyboard controller
Remote Control	Remote controller addressable up to 255 NVRs (Optional)
Mouse	Mouse click, drag and scroll
Microphone	USB Mic (Optional)
WiFi / 4G Dongle	WiFi and 4G external USB dongle supported (Certified brand only)
USB GPS Receiver	Support

Others	
CPU	ARM Cortex A9 Dual Core
OS	Embedded Linux Kernel 4.9
WDT	Hardware watchdog timer
CE	Yes, EMI Class B
FCC	Yes, EMI Class B

Power and working environment	
Power supply	DC 48V 2A 120W (Max) for HDDs and cameras
NVR Consumption (without HDD)	5°C ≤ 8 ≤ 8W
Operating Temperature	0°C ~ 45°C
Operating Humidity	5% ~ 80%
Dimension (W×L×H)	360 × 316 × 60 mm
Weight	≈2.4 KG (Without hard drive)